

SWIVELS

Series traveling blocks conform to API Spec. 8A , Spec.8C and industry standard SY/T5530,and are granted the right to use API monogram.

TECHNICAL FEATURES

- According to user demand, matching of pup joint of alloyed steel material.
- Wash pipe and packing device are of cartridge, integral type structure, convenient to replace;
- With API 4LP hose joint.



TECHNICAL PARAMETER

Model		SL135	SL170	SL225	SL450	SL675
Max. Static load, kN		1350	1700	2250	4500	6750
Max. Speed,r/min		300	300	300	300	300
Max. Working pressure, MPa		35	35	35	35	52
Hook clearance, mm		64	64	75	75	102
Sub thread	To stem API	4 1/2" REG, LH	4 1/2" REG, LH	6 5/8" REG, LH	7 5/8" REG, LH	8 5/8" REG, LH
	To Kelly API	6 5/8" REG, LH	6 5/8" REG, LH	6 5/8" REG, LH	6 5/8" REG, LH	6 5/8" REG, LH
Overall dimensions (Lx W x H) ,mm		2505 × 758 × 840	2786 × 706 × 791	2880 × 1010 × 1110	3035 × 1096 × 1110	3775 × 1406 × 1240
Weight,kg		1341	1834	2815	3060	6880
Note: swivels include two types, swivels with spinner(multi-purpose) and swivels without spinner.						