



TZG-130 Telescopic Boom Iron Roughneck

It is used for makeup and breakout the drill pipe and tool joint. It is the best wellhead equipment for achieved oilfield mechanic modernization.

Technical Features

- Program control, easy to operate. It can finish the makeup and breakout work automatically by one click, and also can operate separately by using emergency operation mode button.
- The operator can control all the functions far away from the wellhead area by remote controller.



- · It can program the positions from itself to wellhead, mouse hole and other place.
- · Compared with other like products, it has higher spinning and breakout torque.
- · Easy to finish the makeup and breakout works over wellhead and mouse hole.
- \cdot It can easy rotate in 270° range for give some space while necessary.

Technical parameters

- 1) Tubular range: 3-1/4 ~ 8-1/2 inch (83 ~ 216mm)
- 2) Max breakout torque: 96,000 ft-lb (130, 000 Nm)
- 3) Max makeup torque: 60,000 ft-lb (81,500 Nm)
- 4) Spinner holding range: 3-1/4 ~ 8-1/2 inch (83 ~ 216mm)
- 5) Max spin-in/spin-out torque(5"pipe): 2,370 ft-lb(3,200 Nm)
- 6) Max spinner speed(5" pipe): 80 r/min



11 2186-8010 / 7010-2276 bomcobras@bomcobras.com.br